



No.	Modification content	Reviser	Date

Specification

- Product name: Polyester expandable sleeving
- Material: Polyester
- Working temperature: -50℃~+150℃
- Melting point: 240±10℃
- Color: Black and Grey
- Application: It is mainly used to cover cables, wire harnesses, tubes, industrial hoses where is required an good mechanical protection.
- Cutting tool: Hot Knife
- Approval: UL , RoHS, REACH, Halogen Free

Part No.	Nominal size (W)		Qty /Bundle	Diameter of monofilament	Expanded range		Packing (m/spool)
	Inch	mm			Min.(I)	Max(O)	
003	1/8 "	3	1	0.25mm	1	6	1000
006	1/4"	6	3	0.25mm	3	9	500
008	5/16"	8	3	0.25mm	5	12	350
010	3/8"	10	3	0.25mm	7	17	350
012	1/2"	12	3	0.25mm	8	20	300
016	5/8"	16	3	0.25mm	10	27	250
019	3/4"	19	3	0.25mm	14	30	200
025	1"	25	3	0.25mm	18	33	200
032	1-1/4"	32	3	0.25mm	20	50	150
038	1-1/2"	38	4	0.25mm	30	60	100
045	1-3/4"	45	4	0.25mm	35	75	100
050	2"	50	5	0.25mm	40	80	100
064	2-1/2"	64	3	0.38mm	45	105	100
076	3"	76	4	0.38mm	64	120	100



Manufacturer	JDDTECH[®] SHENZHEN JDD TECH NEW MATERIAL CO., LTD ADD: Building 2, E zone, Minzhu Western Industrial Area, Shajing Town, Baoan District, Shenzhen city, Guangdong Province, China TEL: 0755-33666001 Fax: 0755-33807127		
Specification No.	JDDKH17-0107	Unit	mm
Product code	FR	Version	A1
REV.0		Tolerances	X. ±2 .X ±0.2
Prepared	Fenfen Hu	Date	15/11/2018
Checked	Dekui Liu	Date	15/11/2018
Approved	Shujin Yang	Date	15/11/2018

